

DIN55110 Easy To Wear Elastic Net Sleeve / Wire Sleeve UL94V-

2

Our Product Introduction

for more products please visit us on plasticpackagingnet.com

Basic Information

- Place of Origin: China
- Brand Name: Qiaoguang
- Minimum Order Quantity: Negotiation
- Price: Negotiation
- Packaging Details: Carton,Negotiation
- Delivery Time: 2 days after receiving full payment
- Payment Terms: L/C, T/T, Western Union,Paypal,ALiPay
- Supply Ability: 20000pcs



Product Specification

- Specjncation: This Product Is Made Of High-quality Polyester Yarn. Easy To Use, Used For Wire Harness Protection, Good Corrosion Resistance, Easy To Wear, Can Be Bent Arbitrarily, And Has Good Insulation And Aesthetics.
- Operation: Pinch Both Ends Of The Telescopic Tube With Both Hands And Tighten It In The Direction Of The Shaft Diameter, And The Diameter Of The Telescopic Tube Will Increase. - Times More. The Relative Arbitrariness Of The Number Of Guardrails Within A Certain Range
- Customization: Support
- Packing: Carton
- Highlight: wire sleeve ul94v-2, din55110 wire sleeve, din55110 wire routing management & protection



Product Description

Elastic Net Sleeve

1. Material: halogen-free environmentally friendly polyester (PET)
2. Operating temperature: -40~ 85 ° C for normal use
3. Flame retardant grade: UL94V-2
4. Color: black and gray, other colors can be made according to customer requirements
5. Melting point: 245 ± 5
6. Product certification: in line with ROHS and NFF16-101 certification standards, DIN55110 certification
7. Product features: easy to use, used for wire protection, good corrosion resistance, easy to wear, can be bent arbitrarily, and has good insulation and aesthetics.
8. How to use: Pinch both ends of the telescopic mesh tube with both hands and tighten it in the direction of the shaft diameter, and the diameter of the telescopic tube will be more than doubled. The relative arbitrariness of the number of guardrails within a certain range is another major feature of this product. The required length is intercepted by thermal cutting to ensure that the nozzle of the braided pipe is not loose.

Model Specifications	Bending diameter(mm)	Threading diameter(mm)		Packaging
		min.(I)	max.(O)	
S-3	3	Φ2.4	Φ6.3	200M/roll
S-6	6	Φ3.2	Φ11	200M/roll
S-10	10	Φ6.3	Φ13	100M/roll
S-13	13	Φ8.2	Φ19	100M/roll
S-15	15	Φ10	Φ22	100M/roll
S-19	19	Φ13	Φ25	100M/roll
S-25	25	Φ16	Φ35	100M/roll
S-32	32	Φ19	Φ44	50M/roll
S-38	38	Φ24	Φ48	50M/roll
S-45	45	Φ32	Φ70	50M/roll
S-50	50	Φ38	Φ89	50M/roll

 **changzhou qiaoguang electrical appliance co.,ltd.**

 18915890812

 sales@cz-qg.com

 plasticpackagingnet.com

223 Hehai West Road, Xinbei District, Changzhou City, Jiangsu Province, China